

PR Polymers Pty Ltd
142 Mica St,
Carole Park QLD. 4300 Australia
PO Box 300,
Carole Park QLD. 4300 Australia



Voice +61 7 3376 5999
Fax +61 7 3376 5944
Email sales@prpolymers.com
Web www.prpolymers.com
ABN 91097405984

REPLACING CHIP DEFLECTOR



REDUCE RE-DRILLS



- PARK DRILL ON SOUND/LEVEL GROUND



- RAISE TO WORKING HEIGHT AND LEVEL



- LOWER DRILL PIPE TO 200mm ABOVE GROUND
- MAKE WORK AREA SAFE & ISOLATE THE DRILL



- REMOVE CABLE TIES FROM CHAINS AND PULL THROUGH ALL 'T' BRACKETS



- REMOVE DEFLECTOR OVER DRILL BIT
- REUSE METAL PARTS ON NEW CHIP MAT



- WITH AT LEAST 2 PAIRS OF HANDS LIFT THE 'HEAD' OF THE DEFLECTOR OVER THE DRILL BIT



- ATTACH 3 CHAINS INTO 3 'T' BRACKETS ADJUSTED TOO HORIZONTAL (SAME NUMBER OF LINKS WILL BE REQUIRED)



- THE 'TAIL' IS RAISED AND CHAIN ADJUSTED TOO HORIZONTAL.
- AGAIN, SAME NUMBER OF CHAIN LENGTHS REQUIRED



- FINALLY, ROCK DEFLECTOR SIDE TO SIDE TO BE SURE THE DRILL PIPE IS CENTERED IN THE SHEET FOR OPTIMUM WEAR LIFE.
- CABLE TIE THE CHAINS TO PREVENT MOVEMENT WHILE OPERATING